

8026 Color Printer

Meet the demands of the busy office with the Intelliprint 8026.



The Intelliprint 8026 color laser printer delivers 26 ppm in full color and 36 ppm in black and white, increasing the efficiency in your work place.

TallyGenicom's Intelliprint technology ensures professional high quality color output, text graphics, reports, presentations even photographs all in bright vibrant colors.

All this speed and quality is backed up by an extremely robust printer engine and guaranteed reliability you expect from TallyGenicom.

The Intelliprint 8026 boasts an impressive list of paper handling features - a maximum paper capacity of 2350 sheets is achievable, more than enough for any office. Remote management with TallyGenicom's embedded Web server is simple to use, and together with installation utilities, maximizes your productivity.

Intelligent Forms

Like all Intelliprint printers, legacy data is no problem; Intellifilter resident within the Intelliprint 8026 enables true migration from other technologies such as Line printer or SIDM (Serial Dot Matrix). All this without expensive server software changes.

Is Security an issue?

Add compact flash or a micro drive and secure printing is enabled. Just add a PIN code in the printer and collect your output. In addition Job Accounting, Job Library, Collation and the ability to store forms, fonts and logos etc. become possible.

- Fast 26 ppm color, 36 ppm mono
- PCL5C/6 and Adobe PostScript Standard
- Robust monthly workload up to 90,000 pages per month
- Ethernet USB2 and Parallel standard
- Intellifilter forms management
- 1200 dpi for quality business documents
- Duplex standard
- Prints on a variety of media including plain paper, transparencies, thick paper, labels and envelopes

Available Configuration:

Serial RS232 (Projects only)

Features & Specifications

Print Speed	26 ppm color; 36 ppm monochrome
Print Method	Single pass electrophotographic laser
Processor	MIPS R7000 533 Mhz
Resolution	1200 x 1200 dpi
Time To 1st Page	8 seconds
Memory	128MB Standard; Maximum 256MB, 1 slot
Standard Connectivity	USB 2, Ethernet TCP/IP, (10BaseT/ 100BaseT), IEEE Parallel
Optional Connectivity	Serial RS 232 (Projects only)
Standard Emulation	PCL5C, PCL6, Adobe PostScript 3
Print Monitor	Built in Web Server
Fonts	80 PCL Fonts
Consumables	CMY=8,000 images each; K=9,000 images (@ 5% coverage on A4)
STD Paper Handling	150 sheet multipurpose feeder; 500 sheet tray
Opt'l Paper Handling	1 x 500 sheet feeder 2 x 550 sheet feeder
Duplexing	Auto Duplex standard
Paper Type	Plain paper, Heavy paper, Transparencies, Labels, Postcards, Coated and Envelopes
Paper Size	A5, B5, A4, Executive, Letter, Legal
Paper Output	Output capacity 250 sheets face down
Printable Area	4 mm unprintable edge
Physical Weight	Intelliprint 8026DN - 34.5 Kg/76lbs including consumables; Intelliprint 8026DNT - 56 Kg/123.2lbs including consumables
PhysicalSize	Intelliprint 8026 DN - 429mm x 580mm x 457mm, 16.9" x 22.8" x 18"
Power Voltage	EMEA: 220-240V ±10%; US: 110 - 127V ±10%
Power Frequency	EMEA: 50 Hz, US: 60 Hz
Power Consumption	45 Watts in Sleep mode (fuser off), 200 Watts in Standby (fuser on)580 Watts average operation, 1,300 Watts maximum
Compliance	Energy Star Compliant
Workload	Up to 100,000 pages per month maximum; Engine Life - 600,000 pages
Reliability MTBF	100,000 hours
Reliability MTTR	Less than 30 minutes
Forms Software	Intellifilter standard for switching of PostScript forms generated by Planetpress
Drivers	Windows® XP, 2003, 2000, ME, 98se; MAC OS X.x & 9; Linux via PPD
Temperature	5° - 32° C
Humidity	15% - 85% relative humidity, non-condensing
Acoustic	Operating - less than 55 dB(A); Standby - less than 35 dB(A); Sleep - background
Warranty	One year on-site
Option 1	1 x 500 sheet feeder; 2 x 550 sheet feeder
Option 2	Memory exp. 256MB
Option 3	4GB Microdrive



