

## T2250 Serial Printer

### Zero Tear-Off, Zero Skewing And Zero Jams



Printing invoices, shipping bills, bar code labels and reports can impact the bottom line. At 750 cps—430 pages per hour—with workloads to 26,000 pages per month the T2250 are ideal for tough, transaction printing.

The T2250 can be configured optionally with three input tractors. A standard front push tractor and straight paper path load up to 6-part forms with zero tear-off for zero waste, zero skewing and zero jams. A second front tractor and a rear tractor may be added. Back-Room Durability .

The 136-column capacity of the T2250 their rugged design and quiet 53dB (A) operation equip them for the warehouse, the shipping dock or the front desk. Back-room durability combined with front-office 24-wire print quality and a variety of automated performance features make the T2250 a serious solution for demand document printing.

#### **Ideal For Many Markets & Applications.**

Federal, State & Local Government - Print tax forms, payroll checks, expense reports, inventory reports, invoices.

Manufacturing, Transportation, & Distribution - Print pick lists, shipping labels and freight bills. Excellent readability on all industry standard bar codes, including POSTNET. Energy Star compliant and low-cost to own and operate. Rugged design for harsh environments.

#### **Product Highlights**

Low cost/high performance – 750 cps at 15 cpi (430 pages per hour)  
Load up to three forms at once; autoswitch between forms for patient charts, prescription labels, pre-printed forms for billing departments.  
Straight paper path for up to 6-part forms on front tractor.  
Auto-switching parallel and serial interfaces.  
Fully automatic gap adjustment, quick-tear, paper load, and paper parking.  
15 Industry standard bar codes resident including POSTNET.  
8 resident fonts.

Healthcare - Handles a wide variety of media including bar code labels for patient charts, prescription labels, pre-printed forms for billing departments.

---

Available Configuration:

**T2250** - 750 CPS, 24 Wire, 136 Column, Parallel + Serial

## Features &amp; Specifications

<b>Print Speed</b>	At 10, 12, 15 cpi: Draft: 500, 600, 750; NLQ: 180, 220, 135; LQ: 90, 110, 135
<b>Print Method</b>	Serial Impact, Bi-directional
<b>Resolution</b>	360 x 360 DPI
<b>Character Density</b>	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 6, 8, 12 lpi
<b>Char. Line Density</b>	136 at 10 cpi, 163 at 12 cpi, 204 at 15 cpi, 232 at 17.1 cpi, 272 at 20 cpi
<b>Character Sets</b>	256 characters, 20 international sets, IBM PC® and Epson®
<b>Standard Connectivity</b>	Dual Parallel/Serial (Auto-Switching); 64K buffer
<b>Optional Connectivity</b>	Ethernet 10/100 (External); RS-422; 9 to 25 pin Serial Adapter
<b>Standard Emulation</b>	MTPL (including 15 resident bar codes and LCP), IBM® Proprinter XL24, Epson® LQ-2550
<b>Optional Emulation</b>	LA75
<b>Fonts</b>	Std: Draft, Copy Draft; NLQ and LQ: Courier, Roman, San Serif, Cyrillic, OCR A/B. Scaleable LCP font (Accepts downloadable fonts in Epson® and IBM® XL24 format). Bar Codes: Code 2/5, Code EAN 8, Code EAN 13, Code UPCA, Code UPCE, Code Delta-Distance; Code 39, Codabar, Code BCD matrix, Code 11, Code MSI/modified Plessey, Code 128, & Code 128 EAN, POSTNET, LCP
<b>Consumables</b>	5.0 million characters
<b>STD Paper Handling</b>	Friction and push tractor, front feed (straight path for continuous forms and labels), auto paper load, auto quick tear, auto view, full paper parking, auto-gap adjustment (for forms thickness)
<b>Opt'l Paper Handling</b>	Supplemental push tractors (front and/or rear), single-bin automatic sheet feeder front, single-bin automatic sheet feeder rear
<b>Number of Copies</b>	Orig. +5 (front push tractors) without jamming; 3 forms at once and autoswitch between forms without operator intervention
<b>Paper Type</b>	Continuous paper, cut sheets (optional feeder)
<b>Paper Weight</b>	NA
<b>Paper Size</b>	3" - 16" width; 3" - 22" length
<b>Parameter Selection</b>	Front panel menu (32 character LCD) and host programmable (3 separate menu configurations can be stored for access through the interface)
<b>Physical Weight</b>	35 lbs
<b>Physical Size</b>	23.6" x 11.8" x 15.7"
<b>Power Voltage</b>	AC 120V or 220-240V
<b>Power Frequency</b>	60/50 Hz
<b>Power Consumption</b>	40 watts (operating); 15 watts (standby)
<b>Compliance</b>	Energy Star compliant, Ozone-free
<b>Workload</b>	Up to 26,000 pages per month
<b>Reliability MTBF</b>	10,000 hours @ 100% duty cycle
<b>Drivers</b>	Windows 95/98, NT 4.0, 2000, XP, 2003; SAP
<b>Temperature</b>	NA
<b>Humidity</b>	NA
<b>Acoustic</b>	53 dB (A)
<b>Warranty</b>	One Year Return To Depot
<b>Option 1</b>	supplemental push tractors; auto sheet feeder front; auto sheet feeder rear
<b>Option 2</b>	printer stand; paper basket; castors
<b>Option 3</b>	DEC LA75 program pack
<b>Options 4</b>	Ethernet 10/100
<b>Option 5</b>	RS-422 I/O
<b>Note</b>	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used.



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Published Date: 05/05/2006 Copyright © 2006 TallyGenicom, L.P.

4500 Daly Drive, Suite 100  
Chantilly, VA 20151  
T 800.436.4266  
www.tallygenicom.com

