

## 7265 Serial Matrix

Reliability At A Top Speed Of Up To 900 CPS



### **Top Speed Of Up To 900 CPS.**

At a top speed of 900 characters per second, the 7265 keeps pace with the hectic business world where printing is time sensitive and critical. The 7265 produces multi-part invoices, shipping documents or bar code labels at a rate of 40,000 pages per month.

The 7265 is expandable to two front input tractors and can handle up to 7-part forms with a straight paper path resulting in jam-free operation.

### **Ideal For Many Markets & Applications.**

Federal, State & Local Government can print tax forms, payroll checks, expense reports, inventory reports, invoices. TallyGenicom—a well-known vendor to government installations—is an ISO 9001 certified manufacturer. Straight paper path for unattended, jam-free operation.

Manufacturing, Transportation, & Distribution can Print pick lists, shipping labels and freight bills. Excellent readability on all industry standard bar codes, including POSTNET. Energy Star compliant and low-cost to own and operate. Rugged design for harsh environments.

### **Product Highlights**

900 characters per second/540 pages per hour in draft mode  
Near letter quality printing at 300 characters per second!  
Straight paper path for reliable forms handling.  
Up to 6-part forms with no skewing or jamming.  
Automatically adjusts for different forms thickness.  
Automatic quick-tear.  
Long life, 20 million character ribbon for less operator interventions.  
Parallel standard.  
10/100 Ethernet and Serial optional.  
Monthly workload of up to 40,000 pages per month.  
Five configurations stored in non-volatile memory.

---

Available Configuration:

**7265** - 24-wire, Parallel

# Features & Specifications

<b>Print Speed</b>	15 cpi:900/300/150; 12 cpi:720/240/120; 10 cpi:650/200/100 (Draft/NLQ/LQ)
<b>Print Method</b>	Serial Impact Dot Matrix; 136 Column; 5 stored configurations
<b>Resolution</b>	360 x 360 dpi
<b>Throughput</b>	540 pages per hour (ECMA 132/6.91, draft)
<b>Character Density</b>	10,12,15,17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	500 M Characters (draft)
<b>Standard Connectivity</b>	Bi-directional Centronics Parallel
<b>Optional Connectivity</b>	10/100 Ethernet, RS232 Serial
<b>Standard Emulation</b>	GENICOM ANSI, Epson® LQ-2550, Epson® LQ-2170 (ESC P/2), MTPL
<b>Fonts</b>	Draft, Copy Draft, Courier, Roman, Sans Serif, OCR A, OCR B, 15 Bar Codes & scaleable LCP fonts
<b>Consumables</b>	20 M Character Ribbon
<b>STD Paper Handling</b>	Front insertion, Push tractor with paper parking and AGA
<b>Opt'l Paper Handling</b>	Additional front push tractor.
<b>Number of Copies</b>	6-part forms
<b>Paper Type</b>	Continuous
<b>Paper Weight</b>	NA
<b>Paper Size</b>	NA
<b>Physical Weight</b>	42 lbs.
<b>PhysicalSize</b>	24.5" x 10.9" x 16.9"
<b>Power Voltage</b>	AC 230V, 50/60Hz and 120V, 60Hz (selectable)
<b>Power Consumption</b>	60 Watts
<b>Compliance</b>	Energy Star compliant, Ozone-free.
<b>Workload</b>	Up to 40,000 pages per month
<b>Reliability MTBF</b>	10,000 hours @ 25% duty cycle
<b>Drivers</b>	Windows XP, 2000, 2003 Server, 95/98, NT4
<b>Temperature</b>	+10°C to +35°C
<b>Humidity</b>	16% to 73%
<b>Acoustic</b>	53 dB (ISO 7779)
<b>Warranty</b>	One year limited on site. First 90 days - parts, labor and travel
<b>Option 1</b>	RS232 Serial; 10/100 Ethernet
<b>Note</b>	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used.



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Published Date: 05/05/2006 Copyright © 2006 TallyGenicom, L.P.



4500 Daly Drive, Suite 100  
Chantilly, VA 20151  
T 800.436.4266  
www.tallygenicom.com

